ADAPTIVE CHANNEL ALLOCATION IN A FREQUENCY DIVISION MULTIPLEXED SYSTEM


Also published as: Publication number: JP11508417 (T) 1999-07-21 Publication date: WO9701256 (A1) Inventor(s): US5726978 (A) Applicant(s): JP3850878 (B2)
F1974555 (A)
EP0882377 (A1) Classification: - international: H04J11/00; H04L5/02; H04L27/26; H04W16/10; H04J11/00; H04L5/02; H04L27/26; H04W16/00; (IPC1-7): H04Q7/36; more >> H04W16/10; H04L5/00A2A1; H04L5/00C1; H04L5/00C4A; - European:

H04Q7/38C4 Application number: JP19960503792T 19960620

Priority number(s): WO1996SE00814 19960620; US19950493489 19950622

Abstract not available for JP 11508417 (T)
Abstract of corresponding document: WO 9701256 (A1)

A method and system of adaptive channel allocation in a frequency division multiplexed system is provided. In the method and system, a subset of M subcarriers is chosen from a larger set of N subcarriers available for communications on a link. As communications take place on the link, signal quality (C/I) measurements (342) on the subcarriers of the subset of M subcarriers and interference (I) measurements (344) on the subcarriers of the group of N subcarriers are periodically performed. The C/I and I measurements are then used to reconfigure (422) the subset of M subcarriers to reduce co-channel interference on the link.



Data supplied from the ${\it espacenet}$ database — Worldwide